

One chair, multiple functions. Perfect for working, meeting, or training. The LXO's™ lightweight and well-proportioned design is the new standard for ergonomic affordable seating.

## STANDARD FEATURES

- ABLEX™ patterned mesh back provides generous lumbar support and dynamic back movement. Air flows freely through this breathable mesh for added comfort.
- Synchro-tilt mechanism with 3 position tilt-lock, pneumatic height adjustment, seat depth adjustment and tension control (6000).
- Swivel mechanism (6000DS) Pneumatic height adjustment, seat depth adjustment and foot ring.
- Black mesh with graphite frame, arms, base and trim.
- Easy to use, height-adjustable arms for individual comfort and support. Arms can be manually adjusted for horizontal width.
- Energy absorbing dual density ENERSORB™ seat foam reduces sitting fatigue.
- Waterfall seat design gently slopes away from the legs, minimizing pressure on the thighs and promoting good posture.
- Model 6002 standard with oval reinforced tubular steel, graphite finish.
- 5-prong, heavy-duty nylon base.
- 2" carpet casters.
- ANSI/BIFMA approved and TB117-2013 compliant.

## GENERAL INFORMATION

- Upholstery: 1 mt/chair
- Design patented.
- If DS option selected, chair will not tilt.



LXO™ 6000-CH

RATED FOR

136kg



LXO™ 6000



MODEL	DESCRIPTION	1	2	3	4	5	6	7	8	Madras Leather	Princess Leather
6000	Mid Back Task										
6002	Mid Back Sled										



6000

6000-07

6002

6000-DS

6000-DS-07

**OPTIONS**

Description	Suffix	Models
Polished Aluminum Base	CH	6000
Seat Slider <i>(Can not combine with "AA")</i>	SL	6000
4 Way Arm Adjustment <i>(Can not combine with "SL")</i>	AA	6000
3" Carpet Casters	LG	6000
2" Hard Surface Casters	TC	6000
3" Hard Surface Casters	TC3	6000
Self-Locking Casters	LC	6000
Glides	GL	6000
Armless	07	6000, 6002
Sit / Stand Drafting Stool	DS	6000
Silver Mesh Back	SM	All Models

**DIMENSIONS**

Model	Overall Width	Overall Depth	Overall Height	Seat Height	Weight		KD Volume
6000	64.8cm	61cm	90.1cm-104.1cm	40.6cm-53.3cm	22.7kg		.26 cu mt
6002	63.5cm	66cm	89.5cm	44.4cm	18.6kg		.34 cu mt
6000-DS	64.8cm	61cm	104.1cm-124.5cm	55.9cm-76.2cm	22.7kg		.26 cu mt